



CETA[®] PC Drippers



A take apart Pressure Compensating dripper incorporating a turbulent flow path and diaphragm for uniform flow rates over a wide range of operating pressures.

Features

- Low manufacturing coefficient of variation (Cv) provides high performance (conforms to ISO 9261).
- Take apart for easy inspection and cleaning.
- Self-flushing cleaning action at low pressure.
- Insect baffle to minimize risk of blockages.
- 0.16" Barbed range incorporates either 0.12" or 0.16" barbed outlets.
- 0.16" PC Spike & In-Line Spike models to anchor CETA[®] at the plant.

Applications

Pots, planter boxes, balcony patio and landscape applications.

DRIPPERS

PRESSURE COMPENSATING



CETA[®] PC
1 gph Spike
with 0.16" Inlet



CETA[®] PC
1 gph Spike with
0.16" In-Line Inlet

Performance Chart

| Pressure (psi) | Flow (gph) | | |
|----------------|------------|-------|-------|
| | 1/2 gph | 1 gph | 2 gph |
| 5 | 0.41 | 0.76 | 1.47 |
| 10 | 0.51 | 0.92 | 1.80 |
| 15 | 0.54 | 1.00 | 2.08 |
| 20 | 0.57 | 1.07 | 2.08 |
| 25 | 0.59 | 1.12 | 2.11 |
| 30 | 0.61 | 1.15 | 2.13 |
| 35 | 0.61 | 1.17 | 2.14 |
| 40 | 0.61 | 1.16 | 2.13 |
| 45 | 0.60 | 1.15 | 2.11 |
| 50 | 0.59 | 1.13 | 2.07 |

Ordering Information - CETA[®] PC 1 gph Spike

| Base Type | Part Number | Pack Quantity | Packs Per Carton | Carton (lbs) |
|---------------|-------------|---------------|------------------|--------------|
| Spike | 30625 | 25 | 40 | 13.4 |
| In-Line Spike | 30655 | 25 | 40 | 14.4 |

Ordering Information - CETA[®] PC with 0.12" Barb Outlet

| Flow | Part Number | Pack Quantity | Packs Per Carton | Carton (lbs) |
|---------|-------------|---------------|------------------|--------------|
| 1/2 gph | 30515 | 100 | 50 | 24.3 |
| 1 gph | 30525 | 100 | 50 | 24.3 |
| 2 gph | 30535 | 100 | 50 | 24.3 |

Ordering Information - CETA[®] PC with 0.16" Barb Outlet

| Flow | Part Number | Pack Quantity | Packs Per Carton | Carton (lbs) |
|---------|-------------|---------------|------------------|--------------|
| 1/2 gph | 30545 | 100 | 50 | 24.3 |
| 1 gph | 30555 | 100 | 50 | 24.3 |
| 2 gph | 30565 | 100 | 50 | 24.3 |

Specifications

| Dimensions Assembled | | CETA [®] PC with 0.12" & 0.16" Barb Outlet | CETA [®] PC Spike/In-Line Spike |
|-------------------------|------------|---|--|
| HEIGHT | | 1.4" | 5.3" |
| WIDTH | | 0.8" | 1.7"/1.4" |
| DEPTH | | 0.6" | 0.6" |
| WEIGHT (approx.) | | 0.07 oz | 0.18 oz |
| UV STABILIZED MATERIALS | BASE/SPIKE | polypropylene | polypropylene |
| | CAP | polypropylene | polypropylene |
| | DIAPHRAGM | silicone rubber | silicone rubber |
| | ADAPTER | acetal | |
| CONNECTION TYPE: Inlet | | BARB 0.16" | BARB 0.16" |
| Outlet | | BARB 0.12" or 0.16" | SPOUT 0.16" |



CETA[®] PC
1/2 gph
Barb 0.16"
with 0.12" or
0.16" Outlet



CETA[®] PC
1 gph
Barb 0.16"
with 0.12" or
0.16" Outlet



CETA[®] PC
2 gph
Barb 0.16"
with 0.12" or
0.16" Outlet