



A range of spray jets that incorporate a valve to adjust watering coverage and application.

Features

- Choice of spray patterns - 360°, 180°, 90° and Mist.
- Threaded for installation on Asta® Stakes, Asta® Stake Adapter, Micro Stake Assembly and Rigid Risers.
- UV stabilized materials for long life.

Applications

Home and landscaped gardens. Vari-Mist™ is ideal for adjusting overhead watering of plants in hanging baskets.

Performance Chart

Pattern						
			360° x 18	Mist	180°	90°
*Minimum opening size			0.02"	0.05"	0.06"	0.06"
Base & Orifice Size	Pressure (psi)	Flow (gph)	Diameter (ft)		Radius (ft)	
Standard Base Max 0.06"	10	0 - 16.7	0 - 18.4		0 - 6.7	0 - 6.4
	15	0 - 21.0	0 - 22.6		0 - 8.1	0 - 8.1
	20	0 - 24.5	0 - 25.7		0 - 9.5	0 - 9.4
	25	0 - 28.0	0 - 26.7		0 - 10.1	0 - 9.8
	30	0 - 31.0	0 - 26.3		0 - 10.6	0 - 10.3
Mist Base Max 0.014"	10	0 - 4.0		0 - 3.0		
	15	0 - 5.0		0 - 2.6		
	20	0 - 5.9		0 - 2.9		
	25	0 - 6.6		0 - 2.8		
	30	0 - 7.4		0 - 2.6		

*Minimum opening size for Base and Cap given to assist filtration selection.
Ghosted figures indicate a change of performance from spray to mist.



Vari-Jet™
360° x 18 hole
10-32 UNF Thread



Vari-Jet™
180° fan
10-32 UNF Thread



Vari-Jet™ Mist Flex Spray Assembly

Ordering Information - Vari-Jets™

Spray Pattern	Base	Cap Color	Part Number	Pack Quantity	Packs Per Carton	Carton (lbs)
360° x 18 hole	Black 10-32 UNF	Black	13145	50	50	16.2
180° fan	Black 10-32 UNF	Black	13125	50	50	16.2
90° fan	Black 10-32 UNF	Black	13115	50	50	16.2
Mist	Black 10-32 UNF	Black	13195	50	50	16.2

Ordering Information - Vari-Jet™ Mist Flex Spray Assembly

Description	Part Number	Pack Quantity	Packs Per Carton	Carton (lbs)
Vari-Jet™ Mist Flex Spray 12" Assembly	59035	5	100	24.1
Vari-Jet™ Mist Flex Spray 24" Assembly	59045	5	50	24.1

Specifications

Dimensions Assembled	UV Stabilized Materials		Base/Connection Type
HEIGHT	2.0"	CAP	acetal
WIDTH	0.9"	BASE	acetal
WEIGHT (approx.)	0.14 oz	Inlet: 10-32 UNF THREAD	