



# VALVES BLACK BULLET MAX SERIES

## ✓ Superior Material

- Glass-filled nylon construction gives the Black Bullet added strength over conventional PVC valves.
- Pick up a Black Bullet in one hand and any other valve in the other to feel the difference.

## ✓ Multi-Bolt Cover

- Stainless steel bolts easily thread in and out of quality brass inserts.
- Black Bullet installers will tell you they rarely need to open a Weathermatic valve. When you do, it is easy to open and easier to close than most valves using screws or jar tops that are susceptible to stripping, dirt, and grit.

## ✓ Unmatched Manual Bleed

- Send the Black Bullet into action by simply pulling the trigger.
- It's the easiest, driest internal manual bleed in the business that won't flood the valve box.
- No twisting on a solenoid or bleed screw is required.

## ✓ Shocking Shock Cone

- The Black Bullet puts the hammer to water hammer by incorporating a cone-shaped diaphragm base.
- The shock cone interrupts the water flow more gradually than other diaphragms to enable quick valve closure without the damaging effect of water hammer.

## ✓ Revolutionary Reverse Flow Design

- Reverse flow design means the valve fails shut rather than open in the event of diaphragm failure, unlike conventional forward flow valves that fail open.
- Balanced pressure on the diaphragm extends valve life over forward flow valves.



## ✓ 25- Year Track Record

- The Black Bullet track record shows less than a fraction of 1% return rate over 25+ years of reliable performance.

## ✓ Amazing Value for the Price!

- One valve for both clean and dirty water applications. Self-cleaning function is achieved as diaphragm actually flexes during operation to send dirt and debris down the line without the maintenance worry of filters and screens.

## ✓ Standard Dirty Water Operation

- Seasoned installers know that valves are the last place to cut expenses when just one call-back eliminates any cost savings on the job.

## ✓ Best Warranty in the Business

- Unparalleled 10-Year Warranty provides worry-free replacement for twice as long as any other competitor.

### Black Bullet Max Specifications

MODEL	DESCRIPTION	FACTORY INSTALLED OPTIONS (CHOOSE ONE)		INTERNATIONAL MODEL
MAX-DW-10	Dirty Water 1" 24 VAC			MAX-DW-10-ISO (11024FCR-10D-ISO)
MAX-DW-15	Dirty Water 1 1/2" 24 VAC	-XPR	-NP	MAX-DW-15-ISO (11024FCR-15D-ISO)
MAX-DW-20	Dirty Water 2" 24 VAC			MAX-DW-20-ISO (11024FCR-20D-ISO)

**100 gallons** given per valve

Our mission is to deliver clean drinking water to thousands of families in need, and to inspire our partners to put water first in irrigation, design, installation, and maintenance.

Copyright 2020 Weathermatic. All Rights Reserved AD4013\_revD





# VALVES

## BLACK BULLET MAX SERIES

### Black Bullet Max Series

#### DIMENSIONS

VALVE	LENGTH	WIDTH	HEIGHT
MAX-DW-10	5" (12.7 cm)	3.13" (7.95 cm)	4.75" (12.07 cm)
MAX-DW-15	5.75" (14.61 cm)	4.50" (11.43 cm)	4.88" (12.40 cm)
MAX-DW-20	7.25" (18.42 cm)	5" (12.7 cm)	6" (14.24 cm)

#### FLOW RANGE

0.2 to 130 GPM  
0 to 30.0 m<sup>3</sup>/hr

#### ELECTRICAL

24VAC/60HZ	24VAC/50HZ
Inrush: 9.48 VA	Inrush: 10.7 VA
Holding: 5.69 VA	Holding: 7.5 VA

Wiring requires a single lead from the controller to each solenoid, plus a common neutral to all solenoids; type UF wire, U.L. listed, is recommended for all hookups

#### FEATURES

- 10 year trade warranty and 100% water tested
- 225 PSI (15.5 BAR) rating
- S24B high-efficiency solenoid for positive opening at high pressures; includes stainless steel actuator and brass threads for long life
- Reverse flow design for water conservation in the event of failure
- Diaphragm's self cleaning ports constantly flex, inhibiting sand and silt from blocking valve action
- Brass shock cone for smooth operation and reduction of water hammer

Easy-to-use internal manual bleed lever; bleeds valve downstream; has positive stops for open and closed positions

- High-strength glass-filled body and cover with 1/4" stainless steel cover bolts and mating brass body inserts
- Brass non-rising flow control stem throttles valve from full open to closed position
- Excellent for low volume irrigation
- Contamination-resistant (CR)
- Chlorine- and chloramine-resistant EPDM diaphragm material



#### OPTIONS (FACTORY INSTALLED)

- XPR Pressure Regulator—the Weathermatic XPR pressure regulating module senses inlet pressure and maintains constant outlet pressure. (see PRK-24 in valve accessory section for specifications)
- Non-potable alert flow handle may be substituted for the standard flow handle. Add -NP suffix.



#### Black Bullet Max Series Valve Pressure Loss

FLOW GPM	MAX-DW-10 1"	MAX-DW-15 1 1/2"	MAX-DW-20 2"	FLOW M3/HR	MAX-DW-10-ISO 2.54 CM	MAX-DW-15-ISO 3.81 CM	MAX-DW-20-ISO 5.08 CM
0-4	1.2 max			0-0.9	0.08 max		
6	1.4			1.0	0.10		
8	1.6			2.0	0.12		
10	1.7			2.5	0.13		
15	2.0			3.0	0.14		
20	2.3	1.3		5.0	0.18	0.10	
25	3.0	1.6		6.0	0.24	0.12	
30	4.3	1.9		7.0	0.32	0.14	
35	6.0*	2.4		8.0	0.43*	0.17	
40	7.7	3.0	2.3	9.0	0.54	0.21	0.16
45	9.5	3.8	2.4	10.0	0.64	0.26	0.17
50	11.5	4.6	2.6	11.0	0.77	0.31	0.17
55		5.6*	2.7	12.0		0.37*	0.18
60		6.7	2.9	14.0		0.51	0.20
70		9.5	3.3	16.0		0.68	0.23
80		13.0	3.4	18.0		0.90	0.23
90			4.2	20.0			0.29
100			5.2*	22.0			0.34*
110			6.7	24.0			0.42
120			7.7	26.0			0.50
130			8.8	30.0			0.62

\* Minimum recommended flow for valves with XPR option or PRK-24 accessory.



**100 gallons** given per valve

Our mission is to deliver clean drinking water to thousands of families in need, and to inspire our partners to put water first in irrigation, design, installation, and maintenance.

Copyright 2020 Weathermatic. All Rights Reserved AD4013\_revD

