

FLOW-SYNC®

Sensor: **Flow**

FEATURES

- Simple two wire connection to ACC and I-Core® controllers (up to 1000')
- Feeds flow data (gallons or liters) to controller, for flow recording and monitoring purposes
- Robust waterproof construction
- Provides station level flow monitoring for reaction to high or low flow conditions
- Helps prevent damage and waste from leaks and breaks in piping system



SPECIFICATIONS

- Recommended pressure range: 0 to 220 PSI
- Pressure Loss: < 1 PSI
- Wiring: 2 x direct burial, 18 AWG or greater, color-coded or marked for polarity, up to 1000' from controller

Impeller-type flow meter, requires FCT for pipe installation (sold separately)

FLOW-SYNC

Model	Description
HFS*	Hunter Flow-Sync sensor, use with ACC and I-Core controllers, sensor requires FCT for pipe installation.

REQUIRED USER INSTALLED OPTION (SPECIFY SEPARATELY)

Model	Description
FCT-100	1" Schedule 40 sensor (white) receptacle tee
FCT-150	1½" Schedule 40 sensor (white) receptacle tee
FCT-158	1½" Schedule 80 sensor (gray) receptacle tee
FCT-200	2" Schedule 40 sensor (white) receptacle tee
FCT-208	2" Schedule 80 sensor (gray) receptacle tee
FCT-300	3" Schedule 40 sensor (white) receptacle tee
FCT-308	3" Schedule 80 sensor (gray) receptacle tee
FCT-400	4" Schedule 40 sensor (white) receptacle tee

Note:

* Flow-Sync (sensor only) for use with ACC and I-Core controllers. Requires FCT for pipe installation (sold separately).

SENSORS