

1/2" Barbed Fittings (17 mm)

Features

- High-impact plastic
- UV resistant
- For secure and easy installation without glue or clamps
- Fits all 1/2" (17 mm) DIG dripline and polyethylene tubing (.570" ID)
- Available with a combination of threads and barbs
- One-piece construction

Specifications

- Operating pressure: up to 30 PSI (2.1 BAR)
- Material: Acetal



| How to specify | | |
|--------------------------------|-------------|------|
| Model | Description | 17mm |
| Insert coupling | | |
| 15-040 | .570" ID | |
| Insert tee | | |
| 15-041 | .570" ID | |
| Insert elbow | | |
| 15-042 | .570" ID | |
| 1/2" Male adapter tee X barb | | |
| 15-043 | .570" ID | |
| 3/4" Male adapter tee X barb | | |
| 15-044 | .570" ID | |
| 3/4" Female adapter tee X barb | | |
| 15-045 | .570" ID | |

| How to specify | | |
|--|-------------|------|
| Model | Description | 17mm |
| 1/2" Male adapter X barb | | |
| 15-046 | .570" ID | |
| 3/4" Male adapter X barb | | |
| 15-049 | .570" ID | |
| 1/2" Elbow Male adapter X barb | | |
| 15-047 | .570" ID | |
| PVC single starter connector w/ o ring | | |
| 15-048 | .570" ID | |
| Insert barbed cross | | |
| 15-061 | .570" ID | |
| 3/4" Male adapter X barb 'Y' | | |
| 15-063 | .570" ID | |
| Poly barbed connector | | |
| 15-065 | .570" ID | |

1/4" and 1/8" Barbed Fittings

Features

- Secure and easy installation without glue or clamps
- Large inside diameter for maximum flow
- One-piece construction
- UV resistant
- Fits 1/4" and 1/8" (.125"-.190" ID) distribution tubing

Specifications

- Operating pressure: up to 30 PSI (2.1 BAR)
- Material: Acetal

| How to specify | | |
|----------------|------------------|--|
| Model | Description | |
| 25-001 | 1/4" Long barb | |
| 25-002 | 1/4" Tee | |
| 25-003 | 1/4" Elbow | |
| 25-004 | 1/4" Short barb | |
| 25-015 | 1/8" x 1/4" Barb | |

