

NODE

Number of Stations: **1, 2, 4, 6**
 Type: **Battery Operated, Fixed**

FEATURES

- Type: Fixed
- Battery powered with battery-life indicator
- Number of stations: 1, 2, 4, 6
- Enclosure: Waterproof indoor/outdoor body
- Independent programs: 3
- Start times per program: 4
- Max. station run time: 6 hrs
- Master Valve operation (available in 2, 4, 6 station models)
- Solar Panel Kit provides maintenance-free operation
- Programmable Off mode up to 99 days
- Manual Cycle
- Rain sensor bypass
- Warranty period: 2 years
- ▶ Easy Retrieve™ memory
- ▶ Seasonal Adjustment: Global

ELECTRICAL SPECIFICATIONS

- Operates DC-latching solenoids only (P/N 458200)
- P/MV (multi-station module)
- Wired sensor inputs: 1
- Power source: 9-volt battery (up to two) or Solar Panel with charging cell

APPROVALS

- IP68, CE, FCC, C-tick
- ▶ = *Advanced Feature descriptions on page 89*



NODE-100
 (less solenoid)
 Diameter: 3½"
 Height: 2½"



NODE-100-LS
NODE-200
NODE-400
NODE-600
 Diameter: 3½"
 Height: 2½"



NODE-100-VALVE (NPT THREADS)
NODE-100-VALVE-B (BSP THREADS)
 Diameter: 3½"
 Height: 2½"



SPNODE
(Solar Panel Kit)
 Height: 3¼"
 Width: 3"
 Depth: 5/8"

NODE	
Model	Description
NODE-100	Single station controller (DC-latching solenoid included)
NODE-100-LS	Single station controller (DC-latching solenoid not included)
NODE-200	2-station controller (DC-latching solenoid ordered separately)
NODE-400	4-station controller (DC-latching solenoid ordered separately)
NODE-600	6-station controller (DC-latching solenoid ordered separately)
NODE-100-VALVE	Single station controller with PGV-101G valve and DC-latching solenoid (NPT threads)
NODE-100-VALVE-B	Single station controller with PGV-101G-B valve and DC-latching solenoid (BSP threads)

MAXIMUM WIRE RUNS	
Wire Size	Max. Distance (ft.)
18 AWG	100

OPTIONS (SPECIFY SEPARATELY)	
Model	Description
458200	DC-latching solenoid
SPNODE	Solar Panel Kit for NODE

CONTROLLERS