

PRO-SPRAY®

Models: **Shrub, 2", 3", 4", 6", 12"**
 Inlet: **1/2"**

FEATURES

- Models: Shrub, 2", 3", 4", 6", 12"
- Compatible with all female threaded nozzles
- Side inlet (SI) version available in 6" and 12"
- Innovative directional flush plug design
- Warranty period: 5 years
- ▶ Co-molded wiper seal
- ▶ Heavy-duty spring
- ▶ Industry's strongest spray body
- ▶ Innovative seal design
- ▶ Pro-Spray check valve

OPERATING SPECIFICATIONS

- Operational pressure range: 15 to 100 PSI

FACTORY INSTALLED OPTIONS

- Drain check valve (up to 10' of elevation)
- Check valve available on 4", 6", 12"
- Reclaimed water ID cap

USER INSTALLED OPTIONS

- Drain check valve (up to 10' of elevation; P/N 437400SP)
- Reclaimed water ID cap (P/N 458520SP)
- Snap-on reclaimed cover (P/N PROS-RC-CAP)
- ▶ = *Advanced Feature descriptions on page 52*



Pro-Spray Reclaimed

Pro-Spray models include optional factory-installed purple reclaimed caps

PRO-SPRAY® - SPECIFICATION BUILDER: ORDER 1 + 2

1 Models	2 Options
<p>PROS-00 = Shrub Adapter</p> <p>PROS-02 = 2" Pop-up</p> <p>PROS-03 = 3" Pop-up</p> <p>PROS-04 = 4" Pop-up</p> <p>PROS-06-SI = 6" Pop-up with side inlet</p> <p>PROS-06 = 6" Pop-up (no side inlet)</p> <p>PROS-12-SI = 12" Pop-up with side inlet</p> <p>PROS-12 = 12" Pop-up (no side inlet)</p>	<p>(blank) = No option</p> <p>CV = Factory-installed drain check valve (Pop-up models only, 6" and 12" models ordered as CV will come as no side inlet)</p> <p>CV-R = Factory-installed reclaimed body cap (Shrub molded in purple)</p>

Examples:

- PROS-04 = 4" pop-up
- PROS-06 - CV = 6" pop-up, drain check valve
- PROS-12 - CV-R = 12" pop-up, drain check valve, reclaimed body cap



PROS-00
 Retracted height: 1 1/2"
 Inlet size: 1/2"



PROS-02
 Retracted height: 4"
 Pop-up height: 2"
 Exposed diameter: 2 1/4"
 Inlet size: 1/2"



PROS-03
 Retracted height: 5"
 Pop-up height: 3"
 Exposed diameter: 2 1/4"
 Inlet size: 1/2"
 Shut-Off



PROS-04
 Retracted height: 5 7/8"
 Pop-up height: 4"
 Exposed diameter: 2 1/4"
 Inlet size: 1/2"
 Shut-Off



[A] **PROS-06-SI**
 [B] **PROS-06**
 Retracted height: 8 3/4"
 Pop-up height: 6"
 Exposed diameter: 2 1/4"
 Inlet size: 1/2"



[A] **PROS-12-SI**
 [B] **PROS-12**
 Retracted height: 16 1/8"
 Pop-up height: 12"
 Exposed diameter: 2 1/4"
 Inlet size: 1/2"

SPRAYS