

QUICK COUPLING VALVES

Quick Coupling Keys

7640
Quick Coupling Key 3/4"

7641
Quick Coupling Key 1"

Quick Coupling Valves 1"

7642
Quick Coupling Valve with Yellow Non-Locking Cover 1" NPT (25,4 mm)

7642B
Quick Coupling Valve with Yellow Non-Locking Cover 1" BSP (25,4 mm)

7643
Quick Coupling Valve with Yellow Locking Cover 1" NPT (25,4 mm)


7643B
Quick Coupling Valve with Yellow Locking Cover 1" BSP (25,4 mm)

7644
Quick Coupling Valve with Lavender Non-Locking Cover 1" NPT (25,4 mm)

7644B
Quick Coupling Valve with Lavender Non-Locking Cover 1" BSP (25,4 mm)

7645
Quick Coupling Valve with Lavender Locking Cover 1" NPT (25,4 mm)

7645B
Quick Coupling Valve with Lavender Locking Cover 1" BSP (25,4 mm)



FEATURES

Signature quick coupling valves and keys use Acme® threads for slow and steady flow control instead of immediate on/off. All models feature rubber cover. Optional locking cover available. Optional lavender rubber cover identifies reclaimed water site – molded in "RECLAIMED WATER - DO NOT DRINK": in English and Spanish.



Acme® threads provide convenient flow control

QUICK COUPLING KEYS

Model	For Valve Models	ENGLISH			METRIC		
		Thread Size		Height	Thread Size		Height
7640	All models	3/4"	1/2"	5 1/4"	25,4 mm	19,05 mm	13,3 cm
7641	All models	1"	3/4"	5 1/4"	19,05 mm	12,7 mm	13,3 cm

QUICK COUPLING VALVES

Quick Coupler Model	Rubber Cover	Locking Cover	Warning Cover	ENGLISH			METRIC		
				Max Capacity GPM	Bottom Pipe Thread	Overall Height	Max Capacity /m	Bottom Pipe Thread	Overall Height
7642 & B	•			20	1"	3 3/4"	75,7	25,4mm	9,5 cm
7643 & B	•	•		20	1"	3 3/4"	75,7	25,4mm	9,5 cm
7644 & B	•		•	20	1"	3 3/4"	75,7	25,4mm	9,5 cm
7645 & B	•	•	•	20	1"	3 3/4"	75,7	25,4mm	9,5 cm

Swivel ells

8810
3/4" (19,05 mm) FPT x 3/4" (19,05 mm) GHT

8811
1" (25,4 mm) FPT x 3/4" (19,05 mm) GHT

8812
1" (25,4 mm) FPT x 1" (25,4 mm) GHT

8010



8819

Brass automatic drain valve I

8819



FEATURES

8819 Specific:

- Prevents underground line breakage due to freezing
- Solid brass body
- Automatically opens when line pressure drops below three psi
- 1/2" male threads
- 5 year warranty on materials and workmanship