

### SOLENOIDS

Control the Flow

#### Features

- Various thread sizes to fit most brands
- HRJ solenoids are compatible with HRC 990 adapters
- Constructed with glass-filled nylon
- 12" of lead wire

#### Specifications

- 24VAC 50/60 (Cycle/Sec)

#### HRV-XXX-SD-RP Specifications

- Inrush current: 0.45A @ 24VAC
- Holding current: 0.30A @ 24VAC
- Coil resistance: 23 Ω

#### HRB-XXX-SD-RP Specifications

- Inrush current: 0.30 A @ 24VAC
- Holding current: 0.17A @ 24VAC
- Coil resistance: 21 Ω

#### HRJ-XXX-SD-RP Specifications

- Inrush current: 0.32A @ 24VAC
- Holding current: 0.18A @ 24VAC
- Coil resistance: 32 Ω

#### HRJ-SD2-RP Specifications

- Inrush current: 0.36A @ 24VAC
- Holding current: 0.23A @ 24VAC
- Coil resistance: 56 Ω

#### HRP-SD-RP Specifications

- Inrush current: 0.35A @ 24VAC
- Holding current: 0.21A @ 24VAC
- Coil resistance: 59 Ω



HRV-XXX-SD-RP



HRB-XXX-SD-RP



HRJ-XXX-SD-RP



HRJ-SD2-RP



HRP-SD-RP

#### How to Specify

	Model
HRV	Hydro-Rain Valve
HRB	Commercial Valve
HRJ	Jar Top Valve
HRP	Push-fit Valve
	Series
XXX	Placeholder
SD	Solenoid
SD2	2nd Generation Solenoid
	Type
RP	Replacement

#### Models (SKU)

- HRV-XXX-SD-RP (03124)
- HRB-XXX-SD-RP (05103)
- HRJ-XXX-SD-RP (02004)
- HRJ-SD2-RP (03084)
- HRP-SD-RP (02034)