



EHF1295-010-D
Flex pipe 1/2" 100' coil

With a strong product heritage and proven years of performance, this tubing is designed to simplify spray head installation making it ideal for challenging landscapes and hard-to-reach areas.



Conveniently unwinds from center



Consistent flexibility



Strength and durability over time

SUPER BLUE FLEX® PIPE, ASSEMBLIES AND FITTINGS

DURABLE PREMIUM GRADE LINEAR, LOW-DENSITY POLYETHYLENE
Achieves higher psi strength and performance over time vs. competitive products

HIGHLY FLEXIBLE
For ease of use

EASILY UNWINDS FROM CENTER OF COIL
For added convenience

ADDED FEATURES

- Coils are shrink-wrapped for ease of handling
- Low-density design protects tubing from landscape
- Five-year warranty

SPECIFICATIONS

- Maximum working pressure: 120 psi at 100° F
- Inside diameter: .49"
- Outside diameter: .68"
- Wall thickness: .095"
- Nominal size: .50"
- Coil size: 100'

SPECIFYING INFORMATION

EHF1295 - 010-D

MODEL	LENGTH
EHF1295 - 1/2" Super Blue Flex pipe	010-D - 100' coil
Example: A 1/2" Super Blue Flex pipe, 100' coil = EHF1295-010-D	



BLUE FLEX ASSEMBLIES



Available in two popular lengths, these sturdy, flexible assemblies protect spray head risers and pipes from breaking when hit or run over by equipment.

STANDARD 8-INCH LENGTH

Provides greater flexibility and strength than competitors' 6-inch models

PRE-ASSEMBLED

Saves time and money

TAPE-FREE FITTING INSTALLATION

Makes installation faster and easier

FEWER THREADED JOINTS

Minimizes leaks

ADDED FEATURES

- Easily adjusts sprinkler head to required grade
- Compatible for below-grade installation
- Five-year warranty

SPECIFICATIONS

- Operating pressure range: 25-75 psi
- Maximum operating pressure: 85 psi
- Pressure-tested to 120 psi

MODELS

Model	Description
B-FLEX8-05	8" x 1/2" male x 1/2" street ell
B-FLEX12-05	12" x 1/2" male x 1/2" street ell
B-FLEX8-0575	8" x 1/2" male x 3/4" street ell
B-FLEX12-0575	12" x 1/2" male x 3/4" street ell

SPECIFYING INFORMATION

B-FLEX - **XX** - **XXXX**

MODEL	LENGTH	FITTING
B-FLEX - Blue Flex swing assembly	8 - 8" 12 - 12"	05 - 1/2" male x 1/2" street ell 0575 - 1/2" male x 3/4" street ell

Example: A 12" swing assembly with 3/4" street elbow = **B-FLEX12-0575**

ASSEMBLY FRICTION LOSS DATA

MODELS	GPM FLOW						
	1	2	3	4	5	6	7
B-FLEX8-05	0.04	0.11	0.27	0.47	0.85	1.22	1.78
B-FLEX12-05	0.05	0.15	0.36	0.62	1.13	1.62	2.37
B-FLEX8-0575	0.05	0.14	0.31	0.60	1.07	1.65	2.29
B-FLEX12-0575	0.06	0.18	0.41	0.80	1.42	2.20	3.05

BLUE FLEX FITTINGS



ADDED FEATURES

- Five-year warranty

MODELS

Model	Description
FFP-T	1/2" barbed tee
FFP-75EM	3/4" male x 1/2" barb elbow
FFP-50EM	1/2" male x 1/2" barb elbow
FFP-C	1/2" barbed coupler

We reserve the right to improve our products and make changes in the specifications and designs without notice and without incurring obligation. Products depicted in this brochure are for demonstration purposes only. Actual products offered for sale may vary in design and features.