

# 1/2" Barbed Fittings (17 mm)

## Features

- High-impact plastic
- UV resistant
- For secure and easy installation without glue or clamps
- Fits all 1/2" (17 mm) DIG dripline and polyethylene tubing (.570" ID)
- Available with a combination of threads and barbs
- One-piece construction

## Specifications

- Operating pressure: up to 30 PSI (2.1 BAR)
- Material: Acetal



How to specify		
Model	Description	17mm
Insert coupling		
15-040	.570" ID	
Insert tee		
15-041	.570" ID	
Insert elbow		
15-042	.570" ID	
1/2" Male adapter tee X barb		
15-043	.570" ID	
3/4" Male adapter tee X barb		
15-044	.570" ID	
3/4" Female adapter tee X barb		
15-045	.570" ID	

How to specify		
Model	Description	17mm
1/2" Male adapter X barb		
15-046	.570" ID	
3/4" Male adapter X barb		
15-049	.570" ID	
1/2" Elbow Male adapter X barb		
15-047	.570" ID	
PVC single starter connector w/ o ring		
15-048	.570" ID	
Insert barbed cross		
15-061	.570" ID	
3/4" Male adapter X barb 'Y'		
15-063	.570" ID	
Poly barbed connector		
15-065	.570" ID	

# 1/4" and 1/8" Barbed Fittings

## Features

- Secure and easy installation without glue or clamps
- Large inside diameter for maximum flow
- One-piece construction
- UV resistant
- Fits 1/4" and 1/8" (.125"-.190" ID) distribution tubing

## Specifications

- Operating pressure: up to 30 PSI (2.1 BAR)
- Material: Acetal

How to specify		
Model	Description	
25-001	1/4" Long barb	
25-002	1/4" Tee	
25-003	1/4" Elbow	
25-004	1/4" Short barb	
25-015	1/8" x 1/4" Barb	

