

RAIN-CLIK®

Sensor: **Rain**

FEATURES

- Quick Response™ feature shuts the system off as soon as it starts raining
- Maintenance-free design with 10-year battery life for Wireless Rain-Clik
- Adjustable vent ring allows for setting of reset delay
- Rugged polycarbonate housing and metal extension arm
- Rain-Clik includes 25' of 20 AWG sheathed, two-conductor, UL-approved wire
- Wireless unit available with 800' range from wireless sensor to receiver
- Warranty period: 5 years (10 year battery warranty for wireless model)
- Compatible with most controllers

SPECIFICATIONS

- Wiring: normally-open or normally-closed
- Time to turn off irrigation system: 2 to 5 minutes approx. for Quick Response
- Time to reset Quick Response: 4 hours approx. under dry, sunny conditions
- Time to reset when fully wet: 3 days approx. under dry, sunny conditions
- UL listed, CUL (CSA), CE
- Switch rating: 24 VAC, 3 A
- Freeze sensor shuts system off when temperatures fall below 37° F (Rain/Freeze-Clik® model)
- System operating frequency: 433 MHz (wireless model)
- Communication range up to 800' line of sight (wireless model)
- Rain/Freeze-Clik shuts system off when temperatures fall below 37° F
- Receiver input power: 24 VAC (from controller)

APPROVALS

- UL listed, FCC approved, cUL, CSA, CE



RAIN-CLIK
Height: 2½"
Length: 7"



WR-CLIK-TR
Height: 3"
Length: 8"



WR-CLIK-R
(Receiver)
Height: 3¼"
Length: 4"



SGM
Optional gutter mount

RAIN-CLIK	
Model	Description
RAIN-CLIK	Rain-Clik sensor
RFC	Rain/Freeze-Clik sensor
WR-CLIK	Wireless Rain-Clik system
WR-CLIK-TR	Wireless Rain-Clik Transmitter (only)
WRF-CLIK	Wireless Rain/Freeze-Clik system
WR-CLIK-R	Wireless Rain Receiver (only)

USER INSTALLED OPTION (SPECIFY SEPARATELY FROM CONTROLLER)	
Model	Description
SGM	Optional gutter mount (included in the WRF-CLIK)

SENSORS